



# DIRECT DRIVE VARIABLE SPEED AIR COMPRESSOR

INDUSTRIAL  
COMPRESSED  
AIR & GAS  
SOLUTIONS



■ TRY - PE & PECFD SERIES

# TRY - PE SERIES



MODEL	WORKING PRESSURE		FREE AIR DELIVERY		POWER		OUTLET	SOUND LEVEL	DIMENSIONS	WEIGHT
	bar	psig	m³/min	CFM	HP	kW				
TRY7,5PE	8	116	1,13	40			G 1/2"	63		
	10	145	1,06	37	10	7,5	G 1/2"	63	800 x 700 x 850	125
	13	188	0,6	21			G 1/2"	63		
TRY11PE	8	116	1,78	63			G 3/4"	64		
	10	145	1,57	55	15	11	G 3/4"	64	1050 x 750 x 1040	225
	13	188	1,05	37			G 3/4"	64		
TRY15PE	8	116	2,46	87			G 3/4"	65		
	10	145	2,11	74	20	15	G 3/4"	65	1050 x 750 x 1040	240
	13	188	1,60	56			G 3/4"	65		
TRY22PE	8	116	3,75	132			G 1"	67		
	10	145	3,26	115	30	22	G 1"	67	1050 x 800 x 950	300
	13	188	2,4	84			G 1"	67		
TRY30PE	8	116	4,72	166			G 1 1/2"	67		
	10	145	4,14	146	40	30	G 1 1/2"	67	1200 x 900 x 1000	430
	13	188	2,9	102			G 1 1/2"	67		
TRY37PE	8	116	6,33	223			G 1 1/2"	67		
	10	145	5,65	199	50	37	G 1 1/2"	67	1580 x 1160 x 1600	460
	13	188	3,6	127			G 1 1/2"	67		
TRY45PE	8	116	7,3	257			G 2"	67		
	10	145	6,2	218	60	45	G 2"	67	1580 x 1160 x 1600	840
	13	188	5,10	180			G 2"	67		
TRY55PE	8	116	9,00	317			G 2"	67		
	10	145	7,60	268	75	55	G 2"	67	1580 x 1160 x 1600	860
	13	188	6,20	218			G 2"	67		
TRY75PE	8	116	12,30	433			G 2"	70		
	10	145	10,50	370	100	75	G 2"	70	1580 x 1160 x 1600	930
	13	188	9,00	317			G 2"	70		

# TRY - PECFD SERIES



MODEL	WORKING PRESSURE		FREE AIR DELIVERY		POWER		OUTLET	SOUND LEVEL	DIMENSIONS	WEIGHT
	bar	psig	m³/min	CFM	HP	kW				
TRY7,5PECFD	8	116	1,13	40			G 1/2"	63		
	10	145	1,06	37	10	7,5	G 1/2"	63	800 x 700 x 850	125
	13	188	0,6	21			G 1/2"	63		
TRY11PECFD	8	116	1,78	63			G 3/4"	64		
	10	145	1,57	55	15	11	G 3/4"	64	1050 x 750 x 1040	225
	13	188	1,05	37			G 3/4"	64		
TRY15PECFD	8	116	2,46	87			G 3/4"	65		
	10	145	2,11	74	20	15	G 3/4"	65	1050 x 750 x 1040	240
	13	188	1,60	56			G 3/4"	65		
TRY22PECFD	8	116	3,75	132			G 1"	67		
	10	145	3,26	115	30	22	G 1"	67	1050 x 800 x 950	300
	13	188	2,4	84			G 1"	67		